



ROTWELD®

INVERTER WELDING MACHINE



เครื่องเชื่อมไฟฟ้าอินเวอร์เตอร์



MIG/MMA-200

MIG/MAG-200

Model	Input Voltage	Rated Input Current (KVA)	No Load Output Voltage	Rated Output Voltage	Welding Current (min-max)	No Load Loss(watt)	Electrode Diameter(min)	Duty Cycle (%)	Net Weight (kg)	Dimension (cm)
MIG/MMA-200	AC220V	6.1/7.1	42/56	22/26.4	45-200/20-200	42/56	1.2/4.0	65	19.5	50x23x40
MIG/MAG-200	AC220V	6.1	42	22	45-200	42	1.2	65	23	45x23x40

WELDING GOGGLES

90 degrees flip-up design, hands free during non-welding work.



WG-250F



CHARM-450F

หน้ากากเชื่อมอัตโนมัติ อุปกรณ์เสริมสำหรับช่างมืออาชีพ เพื่อการถนอมสายตา

Optical Class	1/1/1/2
Viewing Area	98x48mm
Cartridge Size	119x112x10mm
Arc Sensor	4
Light State	DIN4
Dark State	Fixed shaden10(11)
Shade Control	Unadjustable
Power On/Off	Fully Automatic
Sensitivity Control	Unadjustable, Auto
UV/IR Protection	Up to Shade DIN16 at All Times